



Safety Data Sheet

Cat. # RC-002

Acrylamide

Size: 500g





acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/29/2015

Revision date: 05/11/2017

Version: 7.1

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : acrylamide, stabilized
CAS-No. : 79-06-1
Product code : 039A
Formula : C3H5NO
Synonyms : 2-propenamide / AAM / acrylagel / acrylamide / acrylamide, monomer / acrylamide, solid / acrylic acid amide / acrylic amide / ethylenecarboxamide / prop-2-enamide / propene amide / propenoic acid amide / vinyl amide
BIG No : 10111

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Chemical raw material
Chemical intermediate

1.3. Supplier

Geno Technology, Inc./ G-Biosciences
9800 Page Avenue
Saint Louis, 63132-1429 - United States
T 800-628-7730 - F 314-991-1504
technical@GBiosciences.com - www.GBiosciences.com

1.4. Emergency telephone number

Emergency number : Chemtrec **1-800-424-9300** (USA/Canada), **+1-703-527-3887** (Intl)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4	H302 Harmful if swallowed
Acute toxicity (dermal) Category 4	H312 Harmful in contact with skin
Acute toxicity (inhalation) Category 4	H332 Harmful if inhaled
Acute toxicity (inhalation:dust,mist) Category 4	H332 Harmful if inhaled
Skin corrosion/irritation Category 2	H315 Causes skin irritation
Serious eye damage/eye irritation Category 2	H319 Causes serious eye irritation
Skin sensitization, Category 1	H317 May cause an allergic skin reaction
Germ cell mutagenicity Category 1B	H340 May cause genetic defects
Carcinogenicity Category 1B	H350 May cause cancer
Specific target organ toxicity (repeated exposure) Category 1	H372 Causes damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 3	H402 Harmful to aquatic life

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H340 - May cause genetic defects
H350 - May cause cancer
H372 - Causes damage to organs through prolonged or repeated exposure
H402 - Harmful to aquatic life

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P272 - Contaminated work clothing must not be allowed out of the workplace
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell
P302+P352 - If on skin: Wash with plenty of water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a poison center or doctor if you feel unwell
P314 - Get medical advice/attention if you feel unwell.
P321 - Specific treatment (see supplemental first aid instruction on this label)
P322 - Specific treatment (see supplemental first aid instruction on this label)
P330 - Rinse mouth.
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Common Name (Synonyms)	Product identifier	%	GHS US classification
acrylamide, stabilized (Main constituent)	2-propenamide / AAM / acrylagel / acrylamide / acrylamide, monomer / acrylamide, solid / acrylic acid amide / acrylic amide / ethylenecarboxamide / prop-2-enamide / propene amide / propenoic acid amide / vinyl amide	(CAS-No.) 79-06-1	100	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspersion pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Take victim to a doctor if irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after ingestion : Rinse mouth with water. Give nothing to drink. Immediately consult a doctor/medical service. Call Poison Information Centre (www.big.be/antigif.htm). Ingestion of large quantities: immediately to hospital. Take the container/vomit to the doctor/hospital.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Toxic if swallowed. Harmful in contact with skin. Causes skin irritation. Harmful if inhaled. Causes serious eye irritation. Caution! Substance is absorbed through the skin.

Symptoms/effects after inhalation : AFTER INHALATION OF DUST/MIST: Coughing.

Symptoms/effects after skin contact : Tingling/irritation of the skin. FOLLOWING SYMPTOMS MAY APPEAR LATER: Skin rash/inflammation. Damp/clammy skin. Impairment of the nervous system. Dizziness. Myasthenia. Sensorial disturbances. Behavioural disturbances. Mental confusion. Disturbances of consciousness. Impaired memory. Tremor. Coordination disorders. Disturbed motor response. Visual disturbances. Change in urine output.

Symptoms/effects after eye contact : Redness of the eye tissue. Lacrimation. Irritation of the eye tissue.

Symptoms/effects after ingestion : FOLLOWING SYMPTOMS MAY APPEAR LATER: Symptoms similar to those listed under skin contact.

Chronic symptoms : Skin rash/inflammation. Feeling of weakness. Loss of weight. Impairment of the nervous system. Symptoms similar to those listed under acute toxicity.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (alcohol-resistant). Water spray if puddle cannot expand.

Unsuitable extinguishing media : Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

5.2. Specific hazards arising from the chemical

Fire hazard : DIRECT FIRE HAZARD: Non-flammable. In finely divided state: increased fire hazard. INDIRECT FIRE HAZARD: Temperature above flashpoint: higher fire/explosion hazard. Substance contains stabilizer against polymerization. Heat destroys stabilizer against polymerization. Reactions involving a fire hazard: see "Reactivity Hazard".

Explosion hazard : DIRECT EXPLOSION HAZARD: Fine dust is explosive with air. INDIRECT EXPLOSION HAZARD: Heat may cause pressure rise in tanks/drums: explosion risk. Dust cloud can be ignited by a spark. Reactions with explosion hazards: see "Reactivity Hazard".

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: seal off low-lying areas. Exposure to fire/heat: have neighbourhood close doors and windows.

Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Face-shield. Protective clothing. Dust cloud production: compressed air/oxygen apparatus. Dust cloud production: dust-tight suit.

Emergency procedures : Mark the danger area. Prevent dust cloud formation. No naked flames. Wash contaminated clothes. In case of reactivity hazard: consider evacuation.

Measures in case of dust release : In case of dust production: keep upwind. In case of dust production: consider evacuation. Dust production: have neighbourhood close doors and windows. In case of dust production: stop engines and no smoking. In case of dust production: no naked flames or sparks. Dust: spark-/explosionproof appliances/lighting equipment.

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the solid spill. Knock down/dilute dust cloud with water spray. Take account of toxic/corrosive precipitation water. Powdered form: no compressed air for pumping over spills.

Methods for cleaning up : Stop dust cloud by covering with sand/earth. Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Powdered: do not use compressed air for pumping over spills. Spill must not return in its original container. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pulverization rapidly increases toxic concentration.

Precautions for safe handling : Avoid raising dust. Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Keep the substance free from contamination. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Powdered form: no compressed air for pumping over. Keep container tightly closed.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

Storage temperature : ambient temperature

Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.

Information on mixed storage : KEEP SUBSTANCE AWAY FROM: combustible materials. oxidizing agents. (strong) acids. (strong) bases. peroxides.

Storage area : Store in a cool area. Store in a dry area. Store in a dark area. Keep out of direct sunlight. Keep container in a well-ventilated place. Provide for a cooling system. Store only in a limited quantity. Store only in a stabilized state. Meet the legal requirements.

Special rules on packaging : SPECIAL REQUIREMENTS: closing. watertight. dry. clean. opaque. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.

Packaging materials : SUITABLE MATERIAL: polyethylene. MATERIAL TO AVOID: steel. aluminium. iron. copper. bronze.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

acrylamide, stabilized (79-06-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH TWA (mg/m ³)	0.03 mg/m ³ (Inhalable fraction and vapor)
--------------------------------	---

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Materials for protective clothing:

GIVE EXCELLENT RESISTANCE: butyl rubber. GIVE GOOD RESISTANCE: nitrile rubber. PVC. viton. GIVE POOR RESISTANCE: natural rubber. neoprene

Hand protection:

Gloves

Eye protection:

Face shield. In case of dust production: protective goggles

Skin and body protection:

Protective clothing. In case of dust production: head/neck protection. In case of dust production: dustproof clothing

Respiratory protection:

Dust production: dust mask with filter type P3. High dust production: self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Crystalline solid. Crystalline powder. Flakes.
Color	: Colourless to white
Odor	: Odourless
Odor threshold	: No data available
pH	: 5.0 - 6.5 (50 %)
Melting point	: 85 °C (1013 hPa)
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: 0.009 hPa (25 °C, OECD 104: Vapour Pressure)
Relative vapor density at 20 °C	: 2.5 (Calculated)
Relative density	: 1.12 (30 °C, Equivalent or similar to EPA OPPTS 830.7300)
Relative density of saturated gas/air mixture	: 1
Specific gravity / density	: 1222 kg/m ³
Molecular mass	: 71.08 g/mol
Solubility	: Soluble in water. Soluble in ethanol. Soluble in ether. Soluble in acetone. Soluble in methanol. Soluble in ethylacetate. Soluble in dimethyl sulfoxide. Water: 215.5 g/100ml (30 °C) Ethanol: 86 g/100ml (30 °C) Acetone: 63 g/100ml (30 °C)
Log Pow	: -0.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Auto-ignition temperature	: Not applicable
Decomposition temperature	: > 85 °C
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Saturation concentration	: 0.026 g/m ³
VOC content	: 0 %
Other properties	: Acid reaction.

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

Violent polymerisation on exposure to (strong) oxidizers: pressure rise and possible bursting of container. Reacts violently with (some) acids/bases. Unstabilized product: polymerizes on exposure to UV light. Violent polymerisation on exposure to temperature rise.

10.2. Chemical stability

Unstable on exposure to light.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Harmful in contact with skin.
Acute toxicity (inhalation) : Harmful if inhaled. Harmful if inhaled.

acrylamide, stabilized (79-06-1)	
LD50 oral rat	354 mg/kg body weight (EU Method B.1: Acute Toxicity (Oral), Rat, Female, Experimental value, 50 % aqueous solution, Oral, 14 day(s))
ATE US (oral)	354 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.
pH: 5.0 - 6.5 (50 %)
Serious eye damage/irritation : Causes serious eye irritation.
pH: 5.0 - 6.5 (50 %)
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : May cause genetic defects.
Carcinogenicity : May cause cancer.

acrylamide, stabilized (79-06-1)	
National Toxicology Program (NTP) Status	Reasonably anticipated to be Human Carcinogen

Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified
Specific target organ toxicity – repeated exposure : Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Potential Adverse human health effects and symptoms : Toxic if swallowed. Harmful in contact with skin. Causes skin irritation. Harmful if inhaled. Causes serious eye irritation. Caution! Substance is absorbed through the skin.
Symptoms/effects after inhalation : AFTER INHALATION OF DUST/MIST: Coughing.
Symptoms/effects after skin contact : Tingling/irritation of the skin. FOLLOWING SYMPTOMS MAY APPEAR LATER: Skin rash/inflammation. Damp/clammy skin. Impairment of the nervous system. Dizziness. Myasthenia. Sensorial disturbances. Behavioural disturbances. Mental confusion. Disturbances of consciousness. Impaired memory. Tremor. Coordination disorders. Disturbed motor response. Visual disturbances. Change in urine output.
Symptoms/effects after eye contact : Redness of the eye tissue. Lacrimation. Irritation of the eye tissue.

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after ingestion	: FOLLOWING SYMPTOMS MAY APPEAR LATER: Symptoms similar to those listed under skin contact.
Chronic symptoms	: Skin rash/inflammation. Feeling of weakness. Loss of weight. Impairment of the nervous system. Symptoms similar to those listed under acute toxicity.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008.
Ecology - air	: Not included in the list of substances which may contribute to the greenhouse effect (IPCC). Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Photooxidation in the air. Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).
Ecology - water	: Harmful to crustacea. Slightly harmful to fishes. Slightly harmful to algae.

acrylamide, stabilized (79-06-1)

LC50 fish 1	180 ppm (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	98 mg/l (EPA 660/3 - 75/009, 48 h, Daphnia magna, Flow-through system, Fresh water, Experimental value, Nominal concentration)

12.2. Persistence and degradability

acrylamide, stabilized (79-06-1)

Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.97 g O ₂ /g substance
Chemical oxygen demand (COD)	1.3 g O ₂ /g substance
ThOD	2.14 g O ₂ /g substance
BOD (% of ThOD)	0.45

12.3. Bioaccumulative potential

acrylamide, stabilized (79-06-1)

BCF fish 1	25.7 mg/kg (480 h, Oryzias latipes)
BCF fish 2	7.4 mg/kg (960 h, Cyprinus carpio)
Log Pow	-0.9 (Experimental value, Equivalent or similar to OECD 117, 20 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

acrylamide, stabilized (79-06-1)

Log Koc	0.551 - 0.755 (log Koc, SRC PCKOCWIN v2.0, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Waste treatment methods.
Product/Packaging disposal recommendations	: Do not discharge into the sewer. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Remove to an authorized incinerator equipped with an afterburner and a flue gas scrubber with energy recovery. Obtain the consent of pollution control authorities before discharging to wastewater treatment plants.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN2074 Acrylamide, solid, 6.1, III
UN-No.(DOT)	: UN2074
Proper Shipping Name (DOT)	: Acrylamide, solid
Class (DOT)	: 6.1 - Class 6.1 - Poisonous materials 49 CFR 173.132
Packing group (DOT)	: III - Minor Danger
Hazard labels (DOT)	: 6.1 - Poison



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 213
DOT Packaging Bulk (49 CFR 173.xxx)	: 240
DOT Special Provisions (49 CFR 172.102)	: IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2). IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner. T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 153
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 100 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 200 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 12 - Keep as cool as reasonably practicable
Other information	: No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Transport document description (IMDG)	: UN 2074 acrylamide, solid, 6.1, III
UN-No. (IMDG)	: 2074
Proper Shipping Name (IMDG)	: acrylamide, solid
Class (IMDG)	: 6.1 - Toxic substances
Packing group (IMDG)	: III - substances presenting low danger
EmS-No. (1)	: F-A
EmS-No. (2)	: S-A

Air transport

Transport document description (IATA)	: UN 2074 Acrylamide, solid, 6.1, III
UN-No. (IATA)	: 2074

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA)	: Acrylamide, solid
Class (IATA)	: 6.1 - Toxic Substances
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

acrylamide, stabilized (79-06-1)	
Not listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb 1,000lb if the substance is solid in powder form with particle size less than 100 microns, or is in solution or molten form

15.2. International regulations

CANADA

EU-Regulations

National regulations

acrylamide, stabilized (79-06-1)	
Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)	

15.3. US State regulations

acrylamide, stabilized (79-06-1)	
U.S. - California - Proposition 65 - Carcinogens List	Yes
U.S. - California - Proposition 65 - Developmental Toxicity	Yes
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Yes
No significant risk level (NSRL)	140

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/11/2017

Full text of H-phrases:


H302	Harmful if swallowed
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H340	May cause genetic defects
H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

acrylamide, stabilized

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
- NFPA fire hazard : 2 - Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur.
- NFPA reactivity : 2 - Materials that readily undergo violent chemical change at elevated temperatures and pressures.



SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.