



Safety Data Sheet

Cat. # RC-059

Guanidine Thiocyanate

Size: 500g





guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/09/2015

Revision date: 05/11/2017

Version: 7.1

SECTION 1: Identification

1.1. Identification

Product form	: Substance
Substance name	: guanidine thiocyanate
CAS-No.	: 593-84-0
Product code	: 218G
Formula	: CH5N3.CHNS
Synonyms	: guanidine hydrothiocyanate / guanidine monothiocyanate / guanidinium rhodanide / guanidinium thiocyanate / guanidium thiocyanate / thiocyanic acid, compd. with guanidine (1:1) / USAF EK-705
BIG No	: 33762

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Geno Technology, Inc./ G-Biosciences
9800 Page Avenue
Saint Louis, 63132-1429 - United States
T 800-628-7730 - F 314-991-1504
technical@GBiosciences.com - www.GBiosciences.com

1.4. Emergency telephone number

Emergency number : Chemtrec **1-800-424-9300** (USA/Canada), **+1-703-527-3887** (Intl)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4	H302 Harmful if swallowed
Acute toxicity (inhalation) Category 4	H332 Harmful if inhaled
Skin corrosion/irritation Category 1C	H314 Causes severe skin burns and eye damage
Hazardous to the aquatic environment - Acute Hazard Category 3	H402 Harmful to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412 Harmful to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H302+H332 - Harmful if swallowed or if inhaled
H314 - Causes severe skin burns and eye damage
H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a poison center or doctor
P312 - Call a poison center or doctor if you feel unwell
P321 - Specific treatment (see supplemental first aid instruction on this label)
P330 - Rinse mouth.
P363 - Wash contaminated clothing before reuse.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent

Name	Common Name (Synonyms)	Product identifier	%	GHS US classification
guanidine thiocyanate (Main constituent)	guanidine hydrothiocyanate / guanidine monothiocyanate / guanidinium rhodanide / guanidinium thiocyanate / guanidium thiocyanate / thiocyanic acid, compd. with guanidine (1:1) / USAF EK-705	(CAS-No.) 593-84-0	100	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1C, H314 Aquatic Acute 3, H402 Aquatic Chronic 3, H412

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Wash immediately with lots of water (15 minutes)/shower. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply neutralizing agents. Take victim to an ophthalmologist.

First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Immediately consult a doctor/medical service. Call Poison Information Centre (www.big.be/antigif.htm). Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns. Harmful if inhaled. Causes serious eye damage.

Symptoms/effects : Nausea. Vomiting. Coordination disorders. Cramps/uncontrolled muscular contractions. Disturbances of consciousness. Narcosis. Dizziness.

Symptoms/effects after inhalation : Corrosion of the upper respiratory tract.

Symptoms/effects after skin contact : Caustic burns/corrosion of the skin.

Symptoms/effects after eye contact : Corrosion of the eye tissue.

Symptoms/effects after ingestion : Possible esophageal perforation. Burns to the gastric/intestinal mucosa.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Quick-acting ABC powder extinguisher. Class A foam extinguisher. Water (quick-acting extinguisher, reel). Water. Class A foam.
- Unsuitable extinguishing media : Quick-acting BC powder extinguisher. Quick-acting CO2 extinguisher.

5.2. Specific hazards arising from the chemical

- Fire hazard : DIRECT FIRE HAZARD: Non-flammable. Most organic solids may burn if strongly heated.
INDIRECT FIRE HAZARD: Heating increases the fire hazard.
- Explosion hazard : DIRECT EXPLOSION HAZARD: Most organic solids are liable to dust explosion hazard.

5.3. Special protective equipment and precautions for fire-fighters

- Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.
- Firefighting instructions : Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.
- Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Face-shield. Protective clothing. Dust cloud production: compressed air/oxygen apparatus. Corrosion-proof suit. Reactivity hazard: compressed air/oxygen apparatus.
Reactivity hazard: gas-tight suit.
- Emergency procedures : Mark the danger area. Prevent dust cloud formation, e.g. by wetting. No naked flames. In case of hazardous reactions: keep upwind. In case of reactivity hazard: consider evacuation. Wash contaminated clothes.
- Measures in case of dust release : In case of dust production: keep upwind. Dust production: have neighbourhood close doors and windows.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Dam up the solid spill. Knock down/dilute dust cloud with water spray. If reacting: dilute toxic gas/vapour with water spray. Take account of toxic/corrosive precipitation water. On heating: dilute combustible/toxic gases/vapours.
- Methods for cleaning up : Prevent dust cloud formation. Scoop solid spill into closing containers. Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid raising dust. Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Thoroughly clean/dry the installation before use. Powdered form: no compressed air for pumping over. Do not discharge the waste into the drain. Keep container tightly closed.
- Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.

guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Information on mixed storage	: KEEP SUBSTANCE AWAY FROM: oxidizing agents. (strong) acids. (strong) bases. peroxides. water/moisture.
Storage area	: Store in a dry area. Store in a dark area. Keep container in a well-ventilated place. Meet the legal requirements. Provide for a tub to collect spills. May be stored under inert gas.
Special rules on packaging	: SPECIAL REQUIREMENTS: closing. clean. opaque. watertight. dry. correctly labelled. meet the legal requirements.
Packaging materials	: SUITABLE MATERIAL: glass. Teflon. polyethylene. MATERIAL TO AVOID: metal.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

guanidine thiocyanate (593-84-0)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Materials for protective clothing:

GIVE GOOD RESISTANCE: nitrile rubber

Hand protection:

Protective gloves against chemicals (EN374)

Eye protection:

Face shield. In case of dust production: protective goggles

Skin and body protection:

In case of dust production: head/neck protection. Corrosion-proof clothing

Respiratory protection:

Dust production: dust mask with filter type P3. High dust production: self-contained breathing apparatus

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Solid.
Color	: White
Odor	: Odourless
Odor threshold	: No data available
pH	: 4.5 - 7.0 (70 %)
Melting point	: 118 - 121 °C
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: < 0.0000001 hPa (20 °C, EU Method A.4: Vapour Pressure)
Relative vapor density at 20 °C	: Not applicable
Relative density	: Not applicable
Specific gravity / density	: 1290 kg/m ³ (25 °C)
Molecular mass	: 118.16 g/mol
Solubility	: Soluble in water. Water: 63.6 g/100ml (25 °C, Equivalent or similar to OECD 105: Water Solubility)
Log Pow	: -1.11 (Calculated, EU Method A.8: Partition Coefficient, 25 °C)

guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (some) acids: release of (highly) toxic gases/vapours.

10.2. Chemical stability

Unstable on exposure to light. Hygroscopic.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Harmful if inhaled.

guanidine thiocyanate (593-84-0)	
LD50 oral rat	354 - 593 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (24 h, Rabbit, Male / female, Experimental value, Skin, 14 day(s))
LC50 inhalation rat (mg/l)	> 0.9 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 14 day(s))
ATE US (oral)	354 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation	: Causes severe skin burns and eye damage. pH: 4.5 - 7.0 (70 %)
Serious eye damage/irritation	: Eye damage, category 1, implicit pH: 4.5 - 7.0 (70 %)
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified

guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic	: No data available
Potential Adverse human health effects and symptoms	: Harmful if swallowed. Harmful in contact with skin. Causes severe skin burns. Harmful if inhaled. Causes serious eye damage.
Symptoms/effects	: Nausea. Vomiting. Coordination disorders. Cramps/uncontrolled muscular contractions. Disturbances of consciousness. Narcosis. Dizziness.
Symptoms/effects after inhalation	: Corrosion of the upper respiratory tract.
Symptoms/effects after skin contact	: Caustic burns/corrosion of the skin.
Symptoms/effects after eye contact	: Corrosion of the eye tissue.
Symptoms/effects after ingestion	: Possible esophageal perforation. Burns to the gastric/intestinal mucosa.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Harmful to aquatic life with long lasting effects. Harmful to aquatic life.
Ecology - air	: Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).
Ecology - water	: Harmful to crustacea. Harmful to fishes. Slightly harmful to algae.

guanidine thiocyanate (593-84-0)	
LC50 fish 1	89.1 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	42.4 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)

12.2. Persistence and degradability

guanidine thiocyanate (593-84-0)	
Persistence and degradability	Not readily biodegradable in water.

12.3. Bioaccumulative potential

guanidine thiocyanate (593-84-0)	
Log Pow	-1.11 (Calculated, EU Method A.8: Partition Coefficient, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

guanidine thiocyanate (593-84-0)	
Surface tension	Data waiving
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Waste treatment methods.
Product/Packaging disposal recommendations	: Remove to an authorized plant for the destruction, neutralization and elimination of hazardous waste. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1759 Corrosive solids, n.o.s. (Guanidinium thiocyanate), 8, III
--------------------------------	---

guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No.(DOT) : UN1759
Proper Shipping Name (DOT) : Corrosive solids, n.o.s.
Guanidinium thiocyanate
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 213
DOT Packaging Bulk (49 CFR 173.xxx) : 240
DOT Symbols : G - Identifies PSN requiring a technical name
DOT Special Provisions (49 CFR 172.102) : 128 - Regardless of the provisions of §172.101(c)(12), aluminum smelting by-products and aluminum remelting by-products described under this entry, meeting the definition of Class 8, Packing Group II and III may be classed as a Division 4.3 material and transported under this entry. The presence of a Class 8 hazard must be communicated as required by this Part for subsidiary hazards
IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).
IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.
T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 25 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 100 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Emergency Response Guide (ERG) Number : 154
Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Transport document description (IMDG) : UN 3261 corrosive solid, acidic, organic, n.o.s., 8, III
UN-No. (IMDG) : 3261
Proper Shipping Name (IMDG) : corrosive solid, acidic, organic, n.o.s.
Class (IMDG) : 8 - Corrosive substances
Packing group (IMDG) : III - substances presenting low danger
EmS-No. (1) : F-A
EmS-No. (2) : S-B

Air transport

Transport document description (IATA) : UN 3261 Corrosive solid, acidic, organic, n.o.s., 8, III

guanidine thiocyanate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

UN-No. (IATA)	: 3261
Proper Shipping Name (IATA)	: Corrosive solid, acidic, organic, n.o.s.
Class (IATA)	: 8 - Corrosives
Packing group (IATA)	: III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

guanidine thiocyanate (593-84-0)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

EU-Regulations

National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information


according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/11/2017

Full text of H-phrases:

H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H332	Harmful if inhaled
H402	Harmful to aquatic life
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard : 3 - Materials that, under emergency conditions, can cause serious or permanent injury.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.